







Elegantly bringing the outside inside, the Artline window is art with a purpose - quality, lightness and comfort. Its design implies a conscious effort to create an art object that is both functionally and aesthetically pleasing. Creative both in its design and in its effect on the building and the user, Artline is contempory architecture.


DESIGN

MINIMAL

The impression of extreme simplicity and lightness of Artline is a result of the special attention given to the combined action between glass, frameless windows, elegant lighting and careful architectural consideration of spaces where LIGHT IS MORE. Artline's sophisticated minimalist design creates a light and fluid appearence, even for large fix and openable windows.









FUNCTIONAL

The range of functions that Artline is able to perform is extensive, giving it a high level of practicallity. Floor to ceiling glass walls can easily be opened and closed to let the outside come in. Each vent can carry up to 500 kg, allowing both large and heavy glazed infills. Artline windows can reach up to 3,5 metres in height. The window's impressive sizes coupled with a minimal visible frame width allow building interiors to be flooded with light.





TECHNOLOGY

Artline's state of the art aluminium window technology includes optimal thermal and acoustic insulation, high weather resistance and security solutions. The high level of technology used within Artline frames makes it top performing:

- Security
- Durability
- Transparency (98%)
- Impressive weather performance
- High thermal comfort







ARTLINE

High performance thermally insulated sliding door system with a slim sightline near the meeting stile (26 or 38 mm).

• Vent weight up to 320 kg


- 3 meters high without reinforcement
- Quadruple synthetic or stainless-steel wheels, dustproof ball bearing
- Building depth frame: 125 mm
- Vent depth: 47 mm
- Max. glazing vent: 42 mm
- Minimalistic design
- Complies with $\mathbf{C}\mathbf{E}$ marking
- Burglary resistance class RC2

Performances

| Water, Air & Wind classes | E750 - 4 - C3 |
|--------------------------------------|---------------|
| $U_{w} (U_{g} = 0.7 / \Psi = 0.051)$ | 1,18 |
| $U_{w} (U_{g} = 0.5 / \Psi = 0.039)$ | 0,98 |

 U_w value based on test element of 3000 x 2800 mm





- Vent weight up to 500 kg
- 3,5 meters high without reinforcement
- Quadruple stainless-steel wheels on a double rail, dustproof ball bearing
- Building depth frame: 150 mm
- Vent depth: 57 mm
- Max. glazing vent: 52 mm
- Minimalistic design
- Complies with **C€** marking
- Burglary resistance class RC2


Performances

| Water, Air & Wind classes | 9A - 4 - C3 |
|--------------------------------------|-------------|
| $Uw (U_g = 0.7 / \Psi = 0.051)$ | 1,09 |
| $U_{w} (U_{g} = 0.5 / \Psi = 0.039)$ | 0,91 |

 $\rm U_w$ value based on test element of 3000 x 2800 mm

ARTLINE XL

High performance thermally insulated sliding door system with a slim sightline near the meeting stile (26 or 38 mm).







Your local Sapa Building System fabricator

SAPA BUILDING SYSTEM Service, from design to installation

Sapa Building System, is one of the largest suppliers of aluminium building systems in Europe and is part of the Norwegian group Sapa. The core business is the development and distribution of aluminium profile systems. Sapa Building System aims for well-developed systems and project solutions offering a tangible added value to fabricators, architects, investors and home-owners.

Windows, Doors, Sliding Systems, Curtain Walls, Conservatories, Balustrades, Gates, Solar Shading and BIPV

SAPA BUILDING SYSTEM POLAND SP. Z O.O.

ul. Graniczna 60, 93-428 Łódź
T +48 42 683 63 73 | F +48 42 640 04 26
E info.sbs.pl@sapagroup.com | W www.sapabuildingsystem.pl